LARGE FORMAT UV FLATBED PRINTER

Customized Digital Printing on different size media



4030Pro UV Printer

- -- RICOH GEN5&GEN6 INDUSTRIAL GRADE HEADS
- -- FACTORY&LOCAL PROFESSIONAL SERVICE





Ricoh GEN5 & GEN6
Print Heads



Auto Media Detector Electromagnetic




6 Zones Separated Vaccum Controller



THK Guide Rails Made In Japan




Panasonic Motor&Driver Made In Japan



White Ink Circulation (WithStirring Function)



Al Visual Position Camera



Vaccum Platform With Position Pins

Our factroy was estabilished in 2005's, specilized in UV faltbed printers and printing solutions for different requirements from various industries, The rich experience in uv printers help us to get recognition from customers from all the world.

In 2022, we provided the AI printing system in market, which helps customers who print small with different shapes media to print fastly and easily, till now, more than 10k customers who use this system in printing business. Join us, we will create more digital solutions together.



Professional Factory -- Expore More Printing Solution in Various Industries

ITEMS	SPECIFICATIONS
Model	4030Pro UV PRINTER
Printhead	Industry Grade Ricoh GEN5/GEN6 head
Print Head Number	Max 8 heads
Color Set	CMYK; CMYK+W; CMYK+CMYK;CMYK+W+V; CMYK+W+CMYK
Print Size	4000mm x 3000mm
Print Speed (sqm/h) G5 heads	4PASS 15 sqm/h 4PASS 25 sqm/h 6PASS 12 sqm/h Print Speed (sqm/h) 6PASS 20 sqm/h 8PASS 8 sqm/h 8PASS 15 sqm/h
Print Direction	Unidirection/Bidirection
Media Type	Glass, Acrylic, Wood, Ceramic, Metal Sheet, PVC Sheet, Plastic, 3C product etc.
Media Thickness	Max. 100 mm
InkType	UV Curing Ink (None VOC)
Special Ink	Optional White Ink or Varnish
Curing System	LED Curing System
File Format	TIFF/ JPEG/ POSTSCRIPT3/ PDF
RIP Software	Riprint/Unitedfancy
Data Connector	USB3.0
Power	220VAC(±10%) Single Phase, 50/60 HZ
Power Consumption	6.5 KW
Machine Size/N.W	6.5 m x 3.9 m x 1.45 m, 3000kgs
Packing Size/G.W	4200~mm~x~800~mm~x~850~mm + 3900~mm~x~2300~mm~x~1350~mm + 3900~mm~x~2300~mm~x~1350~mm~,~4000 kgs
Environment Requirement	Seperated, clean, low dust, well-ventilated environment Woring Temperature:20°C-28°C Relative humidity:40%-60%

★ Customized configuration available based on different customers' requirments

Factory: Linyi Yicai Digital Machinery Co., Ltd. Shandong Digitop Technology Co., Ltd.

Contact: Sophia Ju (General Manager)

Address:#2 building,Dingsheng Industrial Park,Linyi city, Shandong,China Email:info@uvprinterbest.com Whatsapp/Wechat:+86 18805392014











